


# MIG 1/CP

9200CP4080MG

**TEC-MAR®**  
LIGHTING



## SPECIFIC PRODUCT

<b>Mod</b>	CP
<b>Color</b>	Silver
<b>Installation</b>	Led street light fitting. Pole and wall mountable
<b>Application</b>	Outdoor
<b>Materials</b>	Die cast aluminium body, coated with polyester anticorrosion powder silver color. 4 mm thick tempered transparent glass, silicon gasket
<b>Insulation class</b>	Class II
<b>Protection index</b>	IP66
<b>Impact degree</b>	IK08
<b>Ambient temperature (Ta)</b>	'-25 / 45 °C
<b>Optics</b>	High performance PMMA EN13201 Class P (Type II/III) cycle/pedestrian optic
<b>Power supply</b>	220-240Vac
<b>Frequency</b>	50/60Hz
<b>Surge protection</b>	10kv
<b>Led modules</b>	Removable (Class: D)
<b>Standard equipment</b>	- 60 mm diameter painted adjustable pole bracket. - 1500 mm long H07RN-F neoprene cable.
<b>Luminous flux maintenance</b>	L90-B10 > 100.000 h
<b>Wiring</b>	Removable
<b>Step Mac Adams</b>	3 step
<b>Photobiological safety class</b>	Risk exempt group
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1
<b>Warranty</b>	7 years

## PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
80	-	4000°K - CRI>70	virtual midnight	12134	152	245	415	60	-	4.5

