


MIG 2/ME

9201ME4104MG

TEC-MAR®
LIGHTING



SPECIFIC PRODUCT

Mod	ME
Color	Silver
Installation	Led street light fitting. Pole and wall mountable
Application	Outdoor
Materials	Die cast aluminium body, coated with polyester anticorrosion powder silver color. 4 mm thick tempered transparent glass, silicon gasket
Insulation class	Class II
Protection index	IP66
Impact degree	IK08
Ambient temperature (Ta)	'-25 / 45 °C
Optics	High performance PMMA EN13201 Class ME asymmetrical streetlight optic
Power supply	220-240Vac
Frequency	50/60Hz
Surge protection	10kv
Led modules	Removable (Class: D)
Standard equipment	- 60 mm diameter painted adjustable pole bracket. - 1500 mm long H07RN-F neoprene cable.
Luminous flux maintenance	L90-B10 > 100.000 h
Wiring	Removable
Step Mac Adams	3 step
Photobiological safety class	Risk exempt group
Trademarks and certifications	CE / UNI EN 60598-1
Warranty	7 years

PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
104	-	4000°K - CRI>70	virtual midnight	17073	164	325	490	65	-	6.7

